

I-TRAC[®] GROUND PROTECTION PANELS, TRANSLUCENT



Heavy-Duty Drivable Flooring for Temporary Roads & Event Access

SKU: 1006110.00 | **Categories:** [Heavy Duty Flooring](#), [Temporary Flooring & Ground Protection](#)



PRODUCT DESCRIPTION

i-Trac[®] is a premium ground protection system designed for events, stadium builds, and job sites where heavy-duty access is required. These modular polypropylene panels interlock seamlessly to form stable temporary roads, vehicle access lanes, and pedestrian walkways—without damaging the underlying turf or soil.

Each panel covers approx. 1.2 m² and supports loads of up to **20 tonnes**, making it one of the most robust temporary roadway solutions available. Lightweight enough for single-person handling and quick, tool-free installation, i-Trac[®] is trusted worldwide for projects where strength, speed, and reliability matter.

Key Features of i-Trac Ground Protection Panels:

- **Extreme Load Capacity** – Supports up to 20 tonnes per panel
- **Turf-Safe Polypropylene** – UV-stabilised, heat-reflective, and designed to protect sensitive grass
- **Quick Installation** – Panels lock together via a cam-and-pin system; no tools required
- **Secure Grip Surface** – Aggressive tread provides traction for vehicles and pedestrians in all weather
- **Modular Flexibility** – Adapts to curves, slopes, and uneven site conditions
- **Lightweight & Portable** – Under 17 kg per panel for fast handling and reduced labour costs
- **Non-Conductive & Non-Corrosive** – Safe for broadcast, electrical, and outdoor environments

Ideal Applications

- Stadium access roads for trucks, forklifts & utility vehicles
- Temporary drivable lanes on grass, soil, gravel, or sand
- Reinforced pedestrian walkways for high-traffic areas
- FOH platforms, production compounds & artist zones
- Event logistics, loading docks & site entrances
- Temporary parking areas or helipad landing pads

TECHNICAL SPECS

Weight	34.3 kg
Dimensions	47.2 × 2.2 × 35.4 m
Material	High-strength polypropylene (UV stabilised)
Colour	Translucent

Load Capacity

Up to 20 tonnes

Connection

Cam-and-pin locking system (tool-free)



ADDITIONAL IMAGES

	
	
	
	

